



Wiring, Printed – Component

COMPANY
CANADIAN CIRCUITS INC
#12
13140 88TH AVE
SURREY, BC V3W 3K3 Canada

E193209

Cond Width		Max		Report		Max									
Min		Cond	SS/	Area	Date	Surface	Assembly	Solder	Solder	Oper		Meets	C		
Min	Edge	Thk	DS/	Diam	After	Mount	Process	Process	Limits	Temp	Flame	UL796	T		
Type	mm	mm	mic	DSO	mm	2022-01-01	Technology	Temp °C	Cycles	°C	sec	°C	Class	DSR	I
Multilayer printed wiring boards															
-M	0.15	0.15	17 Int:68	DS	76.2	No	-	-	-	250	5	130	V-0	All	*
-M1	0.15	0.15	17 Int:68	DS	50.8	No	-	-	-	250	5	130	V-0	All	*
-M2	0.05	0.05	17 Int:102	DS	102.0	No	-	-	-	288	30	130	V-0	All	3
Single layer printed wiring boards															
-01	0.18	0.56	17	DS	20.3	No	-	-	-	260	10	130	V-0	All	-
-02	0.06	0.06	17	DS	102	No	-	-	-	288	10	130	V-0	All	-

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or tradename "CCI" or file number and type designation. May be followed by a suffix to denote factory identification or flammability classification..

Last Updated on 2022-06-18

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."